



EZ DriftCal™ Portable Anemometer - Model Number Matrix

More time at the Face.

Series = EZ DriftCal™ Portable Anemometer

1 = Options



EZDC = EZ DriftCal™ Portable Anemometer;
 The EZ DriftCal™ is the ideal calibration or survey tool to assist in calibrating and configuring Maestro airflow sensors or for mine ventilation surveys.

The simple user interface has clear buttons and a back-lit display to assist the ventilation or instrument technician in simple, real time air flow measurement without the requirement of a calculator, pen and paper to arrive at an average air flow rate across a mine drift or tunnel.

The EZ DriftCal™ is normally added to the end of an extension pole to allow the technician the ability to traverse the entire drift cross section.

Technical Specifications:
 Metric or Imperial Units
 4" vane style primary element
 0.3-20 m/s (1-65 ft/s, 59-3920 ft/min) velocity range
 NTC temperature sensor
 0 to 50°C (32 to 122°F) operating range
 -40 to +85°C (-40 to +185°F) storage temperature range
 50 hour estimated battery life
 soft carrying case

NR = Options not required
EXT1 = EZ Extend™ Pole and EZ Holder™
 Extends from 38" to 70" (pole end to center line of anemometer).
 Cage Compact but Drift Ready in one click of the button.

EXT2 = EZ Extend™ Pole and EZ Holder™
 Extends from 63" to 106" (pole end to center line of anemometer).
 Cage Compact but Drift Ready in one click of the button.

